

TECHNICAL DATA

Model	Focus 50	Focus 70	Focus 90	Focus 130	u.m.
Heat input max (p.c.i)	8,3	10	10	12	kW
Heat input min (p.c.i)	3,3	4	4	5	kW
Exhaust type	B _{AS}				
NOx		4		5	class
Consumption G20 Nom./Red.	0,878/0,349	1,057/0,423		1,269/0,529	m ³ /h
Consumption G31 Nom./Red.	0,654/0,256	0,788/0,315		0,946/0,394	Kg/h
Press. nom. supply G20/G30-G31	20 / 28-30/37				mbar
Press. nom. nozzles G20/G30-G31	11 / 28-30/37			10 / 28-30/37	mbar
Press. nom. nozzles G20/G30-G31 Red.	2/5				mbar
Ø burner nozzle G20/G30-G31	2,6/1,45	2,9/1,6		2,3/1,25	mm
Burner nozzle		1		2	nr.
Pilot nozzle	0,35/0,25				code
Power supply (optional)	6VCC (230VAC)				V
Power input	0				W
Gas connection pipe	3/8" - 10				Ø mm
Remote control battery (nr. 1)	9V PP3				type
Receiver battery (nr. 4)	1,5V AA				type
Electrical protection	IP20				
Gas category	2H - 3+ 3B/P				
Exhaust pipe MIN	180				Ø mm

CONTROLS



Infrared remote control:

- Off appliance.
- On/Thermostat knob regulation.
- Warning light transmission control